



The fastest cut sheet digital duplicator, raising standards to the next level.

Digital duplicator





Introducing the SF9490, the all-new global brand of digital duplicators that meets all kinds of user needs

With our products employed in over 180 countries and regions, RISO has been successfully meeting all user requirements by constantly listening to feedback from our customers in order to continually improve our quality. The SF9490 is an important milestone and a masterpiece of our ceaseless innovation. With the fastest speed plus superior operability and print quality, this advanced model ushers you into a higher dimension of printing.





EASY OPERATION: Refined, full-color control panel design

HIGH DEFINITION: 600 x 600

dpi high-resolution with improved image quality



"Since our print volume is very large, time and cost are major concerns..."

RISO offers outstanding productivity through high speed and low cost even for a wide variety of short-run prints.



World's fastest, ultra-high-speed printing at 190 ppm Improved

Achieving 1000 pages printed in approx. 5 minutes, this is the world's fastest printing speed. This surprisingly rapid rate will efficiently support your heavy paperwork requirements.

		25 minutes
	B&W Photocopiers/Laser Printers (40 ppm)	
	5 minutes	
	SF9490	
l		

Quick Master Making mode NEW

A new function, Quick Master Making mode, shortens the master-making time while still maintaining high image quality.

Heavy-load paper feeding

The paper trays have a capacity of 1000 sheets' for both feeding and receiving, which ensures uninterrupted printing over a longer period.




*When using the following weight of paper; 17-lb bond to 21-lb bond (64gsm to 80gsm)




Overwhelmingly economical print costs

The SF series makes prints from a master. As a result, the more pages generated from each master the lower the cost per print,



Paper saving

Page layout printing combines multiple copies of the same documents, or copies of multiple documents onto a single printed page to save paper. Conveniently condense bulky multiplepage documents in an easy-to-read format. These functions are available when using the printer driver.



Versatile paper printing capability

The SF series accepts a wide range of paper types such as recycled paper, coarse paper, cards and envelopes, giving you the perfect options for any job. These multiple roles expand the scope of your business without installing specialized equipment.



"I wonder if we need a professional operator to run digital duplicators..."

RISO offers simple operations through easy-to-master panel and interface design for everyone.

Redesigned, full-color control panel Improved

New, easy-to-use control panel provides intuitive operation. Functions for printing, copying, scanning and managing data are all at your fingertips, logically arranged for intuitive operation on a large 7-inch color LCD touch screen.





Various printing approaches

The SF series offers various ways of printing, depending on your

- specific requirements.
- Standard equipment of PC-I/F
- Direct printing from a USB flash drive
- General SD card compatible for data





Paper insertion function for easier sorting

The duplicator can be programed to insert a white sheet each time a designated number of pages has been printed. This makes it easier to sort and confirm the amount of documents completed.

Paper Memory Print NEW


Step 1

Using the printer driver function installed on your PC, original data created on the PC can easily be converted into a digital pattern, which can be printed on a sheet of paper with a laser printer. *

Step 2

You can then scan the digital pattern created as in Step 1 through SF9490, and easily retrieve the original data by decoding the digital pattern, achieving the same high quality of output image as that being processed through the PC.

 * A laser printer with 600 dpi or higher resolution is required to achieve this function.



Original data



"We don't want to compromise the beauty of the artwork..."

RISO offers outstanding image quality, providing clear text and better images with smooth gradations.

Image data processing raises the bar for 600x600 dpi scanning and printing

This achieves sharp and clear output with the highest image quality.

Enhanced features for clearer output

High scanning quality NEW

The newly designed scanner attains smooth tonal gradation even with photo images.

• Reduced blown-out highlights via equalized dot description

Improved image-processing function Improved

Decreases image deterioration through improved image processing, delivering clearer output.

- Minimizes blocked-up shadows through enhanced gamma correction
- Sharp outlines with contour enhancement achieved

Ink color variations

21 standard colors, 50 custom colors and special order-made colors are available. A wide range of printing colors can meet the needs of a variety of print jobs.

Red	Bright Red	RISO- Marine Red	Burgundy	Brown	Yellow	Green
Teal	Blue	Medium Blue	RISO-Fed. Blue	Purple	Flat Gold	Orange
Crimson	Hunter Green	Gray	Light Gray	Fluorescent Pink	Fluores. Orange	Gold
[Custom colors]						

Other various functions for optimum output

Auto base control
 Tone smooth function

Four image-processing modes: Line, Photo, Duo, and Pencil

Upgraded high-definition master: RISO MASTER F TYPE HG

More precise master copies can be made for reproducing subtle color gradations, clear photo images and even text written in pencil.



Precise reproduction

"How can we manage the information and consumables?"

RISO supports information and consumables management.



RISO console

The total management system improves convenience by integrating applications in one place. Product, consumables and system information can all be checked easily on your PC.



IC card security NEW

Enhanced security by an optional IC card activation kit. (Separate IC card reader required). Only an authorized user can perform printing, effective to prevent divulging information from confidential documents.



Usage report

The SF series provides RISO Copy Count Viewer for counting users' printouts, useful for understanding expenses and usage restriction. The aggregate results are available via printout, USB flash drive or email.

Model (Darla	MA) (62149(12)	-147.0		8		
Partiel	Ass	•••• [6] m		8		
10	Contraction of	dana da	Ormanama.	Redrond MO	(concentration)	del ancionador i
	0x7+					
	JONED		07167A		1430	
	Mu124		ACCOUNT			
			ACCOUNT			
						2
	06,003		64.20			
14						
13	1000710		14,21			
14						
14	pecki		0.847		1047	0
14			295.03		2104	
	0.2					
			Varsion.			v) (

Text-to-speech reading function of the English instruction manual **NEW**

Parts of the instruction manual can be rendered audibly in English, helping to guide operation for anyone with vision difficulties.

Peerless: Environmental

"The environment is important to us..."

RISO strongly cares about global environmental issues as well.

Energy Saving

Energy system with low power consumption. The SF series consumes 1/10th the energy, compared with ENERGY STAR[®] guidelines.




* Complies with the ErP directive in Europe



Rice bran oil ink NEW

The rice bran oil ink contributes to environment sustainability. Rice bran, which would be otherwise wasted, is a raw material with no VOCs, so after the oil is extracted for the ink. It can subsequently be used as fertilizer or animal feed.



RISO SF9490

Optional Accessories



RISO MF/SF Drum

Card Feed Kit

that may be used.

Compatible with paper

weight 27-lb bond to 221-lb

executive for the kinds of paper

index (100gsm - 400gsm). *Please contact a RISO sales



RISO Auto Document Feeder VII



Compatible with paper weights Deluxe and with doors for



RISO Stand D Type III

convenient storage with a

neat appearance.



RISO Controller IS300



RISO Stand N Type III Sturdy open-front stand also offers convenient storage of consumables.



RISO i Quality System

RISO MASTER F TYPE HG97 RISO MASTER F TYPE HD87 (Ledger: 215 sheets)



RISO INK F TYPE Color (1000 ml)



RISO INK F TYPE HD BLACK (1000 ml)



• Wide Stacking Tray (Allows use of paper up to 21 27/32 inches (555mm) in long edge.)

that may be used.

Envelope Feeder

13-lb bond to 32-lb bond (50gsm

executive for the kinds of pape

- 120gsm). *Please contact a RISO sales

• RISO AUTO-CONTROL STACKING TRAY II

• RISO Printer driver for Macintosh

Specifications

Master Making/Pr		High-speed digital master-making / Fully automatic printing			
Driginal Type	inting methods	Book or sheet			
Ouick Master		Approx. 15 seconds (Letter, long edge feed)			
laster Making	Making mode	Approx. To seconds (Letter, short edge feed) Approx. To seconds (Letter, short edge feed)			
me*1	Normal master	Approx. 17 seconds (Letter, long edge feed)			
	making mode	Approx. 19 seconds (Letter, short edge feed)			
esolution	Scanning	600 dpi × 600 dpi			
501011011	Printing	600 dpi × 600 dpi, Quick Master Making Mode: 600 dpi × 400 dpi			
aximum Scannin	ig Area	11 11/16 inches x 17 inches (297 mm x 432 mm)			
int Paper Weight	t	12-lb bond to 116-lb index (46 gsm to 210 gsm)			
int Paper Size*2		3 15/16 inches x 5 13/16 inches to 12 19/32 inches x 17 inches (100 mm x 148 mm to 320 mm x 432 mm)			
ximum Printing	Area	11 15/32 inches x 16 23/32 inches (291 mm x 425 mm)			
per Feed Tray St	tacking Capacity	1000 sheets'3 (stacking height of 4 11/32 inches [110 mm] or less)			
Paper Receiving Tray Stacking Capacity		1000 sheets'3 (stacking height of 4 11/32 inches [110 mm] or less)			
int Speed*4		7 levels: 60, 80, 100, 120, 130, 160 and 190 sheets per minute			
int Position Adju	stment	Horizontal: ±19/32 inches, Vertical: ±13/32 inches (Horizontal: ±15 mm, Vertical: ±10 mm)			
age Processing	Mode	Line, Photo (Standard/Portrait), Duo (Standard/Line/Photo/Shadow off), Pencil (Darker/Lighter)			
Print Reproduction Ratio		Zoom (50% to 200%), Free, 100% reduction ratio, Margin+ (90% to 99%), Enlargement (200%, 154%, 129%, 121%), Reduction (78%, 65%, 61%, 50%)			
User Interface Functions PC Interface		Color touch panel Image, Contrast, Size, Paper Size Detection, D-Feed Check, Dot Process, Contrast Adj, Tone Curve, Layout, Multi-Up Print, 2 Up, Book Shadow, Top Margin Adj., Binding Margin Adj., Max. Scan, Ink Saving, Quick Master Making, Preview, ADF Semi-Auto ⁵ , Storage, Overlay, Print Speed Adjustment, Print Density Adjustment, Print Position Adjustment, Interval, Renew Page, Auto Page Renewal, Rotate, Special Paper Ctrl, Output reversal, Scanning Side -ADF ⁵ , Paper Memory Print, Program, Job Separation ⁶ , Slip sheet sorting, Job Memory, Reservation, Editor, Idling Action, Confidential, My Direct Access, Meter Display, ID Counter Report, Proof Copy, Direct Printing, USB Job List, Scanning Mode, Admin., Auto Sleep, Auto Power-OFF, Power-OFF Schedule, ECO mode, Protect, RISO iQuality System			
		k Supply		Full automatic (1000 ml/cartridge)	
Master Supply/Disposal		Full automatic Ledger approx. 215 sheets per roll/Disposal capacity: approx. 100 sheets			
wer Source		AC 100-240 V, 50-60 Hz <5.0-2.2 A>			
	Standard	Max. 430 W (AC 100-120 V), 400 W (AC 220-240 V), Ready: 40 W or lower, Sleep: (Standard) 5 W or lower, (Low) 0.5 W or lower. Power-OFF: 0.5 W or lower			
onsumption	Optional Accessories Connected*7	Max. 430 W (AC 100-120 V), 400 W (AC 220-240 V), Ready: 45 W or lower, Sleep: (Standard) 10 W or lower, (Low) 1.5 W or lower, Power-OFF: 0.5 W or lower			
mensions	In use	55 29/32 inches x 27 3/4 inches x 41 15/16 inches (1420 mm x 705 mm x 1065 mm)			
/×D ^{*8} ×H ^{*9})	In storage	30 23/32 inches x 27 3/4 inches x 41 15/16 inches (780 mm x 705 mm x 1065 mm)			
equired Space (W	/×D×H [*])	55 29/32 inches × 51 9/16 inches × 59 21/32 inches (1420 mm × 1310 mm × 1515 mm)			
eight ^{*10}		Approx. 245-lb (111 kg)			
leasurement value v	when set to 100% reproduc	cition ratio. *2 When the optional Wide Stacking Trav is installed, you can use paper up to a size of 13 3/8 inches × 21 27/32 inches (340 mm × 555 mm) by setting (Custom Paper			

*1 Measurement value when set to 100% reproduction ratio. *2 When the optional Wide Stacking Tray is installed, you can use paper up to a size of 13 3/8 inches × 21 27/32 inches (340 mm × 555 mm) by setting [Custom Paper Entry]. Depending on the paper type and paper size, papers may not be aligned properly. *3 When using the following weight of paper; 17-1b bond to 21-1b bond (64gsm to 80gsm) *4 If the temperature of the inside of the print drum (cylinder) is less than 41°F (5°C), [190ppm] is not usable. If the temperature of the inside of the print drum (cylinder) is less than 41°F (5°C), [190ppm] is not usable. *7 When all the following optional accessories are installed. Auto Document Feeder, Job Separator and IC Card Reader. *8 The depth includes the stabilizers for the dedicated rack. *9 The height includes the dedicated rack.

Notes: Specifications are subject to change without notice.

(), CISO, RISO i QualitySystem and red are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries.

Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.

Copyright ©2017 RISO KAGAKU CORPORATION. All rights reserved.



RISO, Inc. 800 District Ave, Suite 390 Burlington, MA 01803 http://us.riso.com/

For more details please contact: